

LightMAX


R0994

48 LED module for flood lighting



5 YEARS WARRANTY

CC CONSTANT CURRENT



FEATURES

- PCB dimension: 170x50mm
- Up to 8475 lm
- Up to 185 lm/W
- CRI 80
- Electrical Insulation 300V
- Up to 12 LED boards in series
- Connection type: WAGO SMD 4-pin 2-P 236C
- Long lifetime up to 80000h
- NIC available on request


APPLICATIONS




Street




Industrial



Downlight



High Bay



Area

LightMAX

R0994

48 LED module for flood lighting



5 YEARS WARRANTY

CC CONSTANT CURRENT

LV 3030HE 3V LED Version

Code	CCT	CRI	Current [mA]	Voltage [V]	Power [W]	Total Lumen [lm]	Lm/W	Energy Efficiency
R0994013080	3000K	80	700	16.6	11.6	2000	172	D
			1050	17.1	17.9	3002	168	D
			1400	17.5	24.5	4010	164	D
R0994014080	4000K		700	16.6	11.6	2140	185	C
			1050	17.1	17.9	3180	178	C
			1400	17.5	24.5	4237	173	C
R0994015080	5000K		700	16.6	11.6	2140	185	C
			1050	17.1	17.9	3180	178	C
			1400	17.5	24.5	4237	173	C

Flux tolerance +/- 10%
 Vf Tolerance +/- 5%
 All values measured: T=65°C

Ask for more information about available LED and other options

HV 3030 6V LED Version

Code	CCT	CRI	Current [mA]	Voltage [V]	Power [W]	Total Lumen [lm]	Lm/W	Energy Efficiency
R0994013080	3000K	80	700	33.3	23.3	4000	172	D
			1050	34.2	35.9	6009	167	D
			1400	34.9	48.8	8025	164	D
R0994014080	4000K		700	33.3	23.3	4279	184	C
			1050	34.2	35.9	6360	177	C
			1400	34.9	48.8	8475	174	C
R0994015080	5000K		700	33.3	23.3	4279	184	C
			1050	34.2	35.9	6360	177	C
			1400	34.9	48.8	8475	174	C

Flux tolerance +/- 10%
 Vf Tolerance +/- 5%
 All values measured: T=65°C

Ask for more information about available LED and other options

LightMAX

R0994

48 LED module for flood lighting



5 YEARS
WARRANTY

CC CONSTANT
CURRENT

LED and board features	
LED number	48
LED type	3030
Circuit	S&P8
Material	Aluminium
Solder	White
Connections	
Cable	AVG 24*8 (0.2 – 0.75mm ²)
Connector	WAGO SMD 4mm ² P 236C
Power	
Ass. Max. input current CC HA 3V	2400 mA
Ass. Max. input current CC 6Volt	1600 mA
Mechanical Data	
H x L	50x170 mm
Thickness	6.1mm
Conditions	
Max. temp. (Ta)	90°C
Max. temp. (Tc)	85°C
Operating temp. Range	-35°C – 80°C

LightMAX

R0994


48 LED module for flood lighting

5 YEARS WARRANTY




CC CONSTANT CURRENT

FLOOD LIGHTING SERIES - DRAWINGS



→ You can check the R0994 Mechanical Drawing [CLICKING HERE](#).

ELECTRICAL CIRCUIT



LightMAX


R0994

Accessories: LedLink Optics lens

5 YEARS WARRANTY




CC CONSTANT CURRENT



Specifications: DVV series	
View Angle (Fwhm)	25°/55°/90° / 50°/25°x145°/45°x140°/45°x155°/60°x145°/60°x155°/70°x 60°
Material	PC 1250Z
Type	6 1
Efficiency	>90%
Operating Temperature	-40°C ~ 110°C

FLOOD LIGHTING SERIES WITH DVV LENS



ASSEMBLY AND SAFETY INFORMATION

Installation must be carried out under observation of the relevant regulations and standards. The LED modules are designed for operation with a casing or luminaire. Installation must be carried out in a voltage-free state (i.e. disconnected from the mains).

The following advice must be observed; non-observance can result in the destruction of the LED assembly modules, fire and/or other hazards.

- o Consider safety regulations acc. EN 60598 in the luminaire design, especially when the operating LED driver is not galvanically isolated.
 - In mode of operation regard to sufficient isolation.
 - Live parts must not be touched in operation mode. Danger in life!
- o ESD (electrostatic discharge) protection measures must be observed when handling and installing the LED modules. See VS's application notes on ESD protection.
- o Adequate anti-static electricity measures, including the use of conductive shoes, ionizers, work bench grounding, wrist straps, flooring and stools should be used.
- o LED assembly modules must not be subjected to any undue mechanical stress, e.g.:
 - do not treat as bulk cargo
 - avoid shear and compressive forces during handling and installation
 - do not damage circuit paths
 - avoid any pressure on the light emitting surface
- o Safe operation only possible by the use of external constant current sources (max. see table 'Electrical Characteristics').
- o Operation only with power supply units that feature the following protection:
 - Short circuit protection
 - Overload protection
 - Overheating protection
- o The module can be fixed with M3 screws. Fixation only with flat or cylinder head screws (M3) (no countersunk screws) Max. torque: 1.2 Nm (M3)
- o Please ensure the correct polarity of the leads prior to commissioning. Reversed polarity can destroy the modules.
- o For interconnection the LED modules is equipped with push-in terminals (WAGO 2050).
- o Safety regulations acc. to EN 60598 (or further standards) has to be observed if the maximum output voltage exceeds the permitted touchable value.
- o The following points must be observed when connecting LED modules in parallel:
 - All LED strings that are wired in parallel must contain the same number of LEDs (symmetrical loading).
 - Owing to differing forward biases, there can be a difference of up to 10% in brightness between modules connected in parallel.
- o To ensure problem-free operation, the specified maximum temperature at the tip point (see 'Operating Life') must be observed (and measured in accordance with EN 60598-1). To satisfy this point, it may be necessary to put measures in place to ensure any heat is dissipated from the PCB to the environment.
- o In the event of outdoor applications or applications in damp locations, care must be taken to protect LED assembly modules against humidity, splashes and jets of water. Any corrosion/damage resulting from humidity or contact with condensation will not be recognized as a defect or manufacturing fault. LED assembly modules are not specially protected against foreign bodies or dust. Depending on the type of application, further protection must be ensured to prevent dust and foreign bodies from entering.
- o Due to the manufacturing process, the PCBs of the LED assembly modules can have sharp edges and corners. Care must therefore be taken during handling and installation to avoid injury.
- o For optimal load of used constant current driver the modules can only be connected in series. The quantity of LED modules is limited by the sum of forward voltage and the capacity of used constant current driver. Safety regulations acc. to EN 60598 has to be observed if the sum of forward voltage exceeds the permitted touchable value.
- o Operating LED modules in the presence of certain chemical substances or in chemically enriched (aggressive) environments can impair module functionality or even cause total module failure.
- o The photobiological safety of the LED modules must be classified into risk groups in accordance with IEC/TR 62778: L_{ns} < group 1 (except HB, 6500 K, > 500 mA: risk group 2

APPLIED STANDARDS

IEC / EN 62031
LED modules for general lighting – Safety specifications

IEC / TR 62778
Application of IEC 62777 for the assessment of blue light hazard to light sources and luminaires