

DotMAX

R3757

24x20mm module, 1 power LED



7 YEARS WARRANTY

CC CONSTANT CURRENT



FEATURES

- PCB dimension: 24x20mm
- Up to 460 lm
- Up to 182 lm/W
- CRI 80, 90
- Max Electrical Insulation 100V
- Max 30 LED boards in series
- Connection type: AVX Poke 2mm 70-9296
- Lifetime > 60 000h @ 700mA
- Suitable for dark light applications
- [5 power LEDs version available \(R1536\)](#)

APPLICATIONS



Indoor



Commercial



Wall Washer

DotMAX

R3757

24x20mm module, 1 power LED



7 YEARS WARRANTY

CC CONSTANT CURRENT

Code	CCT	CRI	Current [mA]	Voltage [V]	Power [W]	Total Lumen [lm]	Lm/W	Energy Efficiency
R3757C02790	2700K	90	350	2,85	0,99	170	170	D
			700	3	2,1	311	148	D
			1050	3,13	3,29	433	131	E
R3757C03090	3000K		350	2,85	0,99	176	176	C
			700	3	2,1	320	152	D
			1050	3,13	3,29	446	136	E
R3757C04090	4000K		350	2,85	0,99	181	181	C
			700	3	2,1	329	157	D
			1050	3,13	3,29	459	139	E
R3757C05090	5000K	350	2,85	0,99	181,4	182	C	
		700	3	2,1	330	157	D	
		1050	3,13	3,29	460	140	E	

*Flux tolerance +/- 10%
**Voltage tolerance +/- 5%

Ask for more information about available LED and other options.

DotMAX

R3757

24x20mm module, 1 power LED



7 YEARS WARRANTY

CC CONSTANT CURRENT

LED and board features	
LED number	-
LED type	3535
Circuit	SI
Material	MCPCB
Solder	Black or White on request
Connections	
Cable	Solid 0,2-0,8mm ² Strand 0,45-0,7mm ²
Connector	2x AVX Poke 2mm 70-9296
Power	
Ass. Max. input current CC	1050mA
Mechanical Data	
H x L	24x20mm
Thickness	3,6mm
Conditions	
Max. temp. (T _o)	90°C
Max. temp. (T _c)	85°C
Operating temp. Range	35°C - 180°C

DotMAX

R3757


24x20mm module, 1 power LED




7 YEARS WARRANTY

CC CONSTANT CURRENT

MECHANICAL DRAWING



ELECTRICAL CIRCUIT



DotMAX

R3757

24x20mm module, 1 power LED





7 YEARS WARRANTY

CC CONSTANT CURRENT



Reflector	
LLGxTD3015 IH1	Linear Reflector 15° SINGLE
LLGxTD3030 IH1	Linear Reflector 30° SINGLE
TypLLGxTD3045 IH1	Linear Reflector 45° SINGLE
Shade	
LLGxTD 30H1 01	Black Cover Single

DRAWING



ASSEMBLY AND SAFETY INFORMATION

Installation must be carried out under observation of the relevant regulations and standards. The LED modules are designed for operation within a casing or luminaire. Installation must be carried out in a voltage-free state (i.e. disconnected from the mains).

The following advice must be observed; non-observance can result in the destruction of the LED assembly modules, fire and/or other hazards.

- o Consider safety regulations acc. EN 60598 in the luminaire design, especially when the operating LED driver is not galvanically isolated.
 - In mode of operation regard to sufficient isolation.
 - Live parts must not be touched in operation mode. Danger in life!
- o ESD (electrostatic discharge) protection measures must be observed when handling and installing the LED modules. See VS's application notes on ESD protection.
- o Adequate anti-static electricity measures, including the use of conductive shoes, ionizers, work bench grounding, wrist straps, flooring and stools should be used.
- o LED assembly modules must not be subjected to any undue mechanical stress, e.g.:
 - do not treat as bulk cargo
 - avoid shear and compressive forces during handling and installation
 - do not damage circuit paths
 - avoid any pressure on the light emitting surface
- o Safe operation only possible by the use of external constant current sources (max. see table 'Electrical Characteristics').
- o Operation only with power supply units that feature the following protection:
 - Short circuit protection
 - Overload protection
 - Overheating protection
- o The module can be fixed with M3 screws. Fixation only with flat or cylinder head screws (M3) (no countersunk screws) Max. torque: 1.2 Nm (M3)
- o Please ensure the correct polarity of the leads prior to commissioning. Reversed polarity can destroy the modules.
- o For interconnection the LED modules is equipped with push-in terminals (WAGO 2050).
- o Safety regulations acc. to EN 60598 (or further standards) has to be observed if the maximum output voltage exceeds the permitted touchable value.
- o The following points must be observed when connecting LED modules in parallel:
 - All LED strings that are wired in parallel must contain the same number of LEDs (symmetrical loading).
 - Owing to differing forward biases, there can be a difference of up to 10% in brightness between modules connected in parallel.
- o To ensure problem-free operation, the specified maximum temperature at the tip point (see 'Operating Life') must be observed (and measured in accordance with EN 60598 1). To satisfy this point, it may be necessary to put measures in place to ensure any heat is dissipated from the PCB to the environment.
- o In the event of outdoor applications or applications in damp locations, care must be taken to protect LED assembly modules against humidity, splashes and jets of water. Any corrosion/damage resulting from humidity or contact with condensation will not be recognized as a defect or manufacturing fault. LED assembly modules are not specially protected against foreign bodies or dust. Depending on the type of application, further protection must be ensured to prevent dust and foreign bodies from entering.
- o Due to the manufacturing process, the PCBs of the LED assembly modules can have sharp edges and corners. Care must therefore be taken during handling and installation to avoid injury.
- o For optimal load of used constant current driver the modules can only be connected in series. The quantity of LED modules is limited by the sum of forward voltage and the capacity of used constant current driver. Safety regulations acc. to EN 60598 has to be observed if the sum of forward voltage exceeds the permitted touchable value.
- o Operating LED modules in the presence of certain chemical substances or in chemically enriched (aggressive) environments can impair module functionality or even cause total module failure.
- o The photobiological safety of the LED modules must be classified into risk groups in accordance with IEC / TR 62778: risk group 1 (except HB, 6500 λ > 500 nm; risk group 2)

APPLIED STANDARDS

IEC / EN 62031
LED modules for general lighting – Safety specifications

IEC / TR 62778
Application of IEC 62777 for the assessment of blue light hazard to light sources and luminaires